



THREE STAGE CYCLONIC FILTRATION. Engineered to prolong filter and blower life, the system is suitable for wet and dry applications. The cyclones use a tuned vortex system in which the outer vortex spiral forces small particles to fall into a separate canister. The filtered stream then passes up through the inner cyclone tube and carried to the final poly filter.



**CAM-OVER REAR DOOR.** Provides a 360-degree positive seal, even under reverse pressure without additional clamping requirements. The highly reliable cam-over door has no in-tank moving parts, so all maintenance is external.



**IN-TANK WASH-DOWN.** Delivers a highpressure water spray to the tank interior helping simultaneously dump material and clean the inside of the tank. Saves clean up time and makes it easier to remove difficult debris.



**LOCKABLE CONTROL PANEL.** All machine controls and gauges are secured and out of the elements.



**NO HASSLE HOSE.** Hang the suction hose on the side of the machine when moving between jobsites instead of coiling or disconnecting it, increasing productivity and reducing operator fatigue.



AUTO BELT TENSIONERS. Keeps proper belt tension at all times and extends belt life.



# VX30 GEN3 300/500/800 Vermeer Vacuum Excavators by McLaughlin

## ENGINE

Make and Model: Kubota V1524B4-1VC1 Fuel Type: Diesel Gross Horsepower: 24.8 hp (18.49 kw) Number of Cylinders: 4 Cooling Method: Water/Antifreeze Fuel Tank: 22 gal (83.3 L) Enclosure: Full Sound Dampening Auto Belt Tensioner: Blower and Water Pump SPOIL TANK Spoil Tank Capacity: 300/500/800 gal (1135/1892/3028 L) Rear Door Type: Cam-Over Hydraulic In-Tank Washdown: Standard Full Tank Shutoff: Mechanical Float/Electric Shut Down Tank Lift Type: Dual Cylinder

#### VACUUM

Filtration: 3 Stage Cyclonic - Standard Final Filter: 2 Micron Washable Filter Vacuum Blower Type: PD Blower Vacuum Blower: 575 cfm (16.28 cm m/min) Vacuum Mercury: 15" hg Hose Length: (2) 15' (457 cm) Hose Diameter: 3" (7.62 cm)

### WATER SYSTEM

Water Pump Flow: 4 gpm (15 L/min) Water Pump Pressure, max: 3,000 psi Clutch Type: Electric Auto Clutch High Pressure Hose Length: 50' (15 m) Low Water Shutoff: Electric

## **GENERAL WEIGHTS & DIMENSIONS: 300 GALLON**

Empty Weight: 5,330 lbs (2,417 kg) Length: 188" (477.52 cm) Width: 98" (248.92 cm) Height: 87" (220.98 cm) Water Tanks: (2) 50 gal (189 L) GVWR: 9,999 lbs Trailer Axles: (2) 6,000 lbs (2,721 kg) **GENERAL WEIGHTS & DIMENSIONS: 500 GALLON** Empty Weight: 5,700 lbs (2,585 kg) Length: 214" (543.56 cm) Width: 98" (756.92 cm) Height: 87" (220.98 cm) Water Tanks: (2) 125 gal (473 L) GVWR: 12,000 lbs

Trailer Axles: (2) 6,000 lbs (2,721 kg)

#### **GENERAL WEIGHTS & DIMENSIONS: 500 GALLON LT**

Empty Weight: 5,570 lbs (2,526 kg) \*Spoil Tank Capacity 425 gal Length: 214" (543.56 cm) Width: 98" (756.92 cm) Height: 87" (220.98) Water Tanks: (2) 50 gal (189 L) GVWR: 9,999 lbs Trailer Axles: (2) 6,000 lbs (2,721 kg)

#### **GENERAL WEIGHTS & DIMENSIONS: 800 GALLON**

Empty Weight: 6,720 lbs (3,042 kg) Length: 237.3" (602.74 cm) Width: 98" (756.92 cm) Height: 91.9" (233.42 cm) Water Tanks: (2) 205 gal (776 L) GVWR: 18,000 lbs Trailer Axles: (2) 9,000 lbs (4,082 kg)

### **GENERAL WEIGHTS & DIMENSIONS: 800 GALLON LT**

Empty Weight: 6,620 lbs (3,002 kg) Length: 237.3" (602.74 cm) Width: 98" (248.92 cm) Height: 91.9" (233.42 cm) Water Tanks: (2) 125 gal (473 L) GVWR: 16,000 lbs Trailer Axles: (2) 9,000 lbs (4,082 kg)

## **AVAILABLE OPTIONS**

Reverse Flow: Standard Strong Arm: Optional Hot Box Water Heater: Only 500/800 non-LT Arrow Board: Optional No Hassle Hose: Optional

#### Specifications subject to change without notice.

Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Navigator and Firestick are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. McLaughlin and the McLaughlin logo are trademarks of McLaughlin Group, Inc. @ 2018 McLaughlin Group, Inc. All Rights Reserved. @ 2018 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.



mclaughlinunderground.com | 864-277-5870

NJPA Contract #070313-VRM GSA Contract #GS-30F-0008S